

EV355228294

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**System And Method For Synchronizing Enhancing  
Content With A Video Program Using Closed  
Captioning**

Inventor(s):  
David Feinleib

ATTORNEY'S DOCKET NO. MS1-132USC1

1     **RELATED APPLICATIONS**

2             This application is a continuation of U.S. serial number 08/779,270, filed  
3     January 6, 1997, which issued as U.S. Patent No. \_\_\_\_\_ on \_\_\_\_\_.

4  
5     **TECHNICAL FIELD**

6             This invention relates to systems and methods for synchronizing enhancing  
7     content with specific junctures in a video program. More particularly, the  
8     invention relates to systems and methods for synchronizing the enhancing content  
9     with the video program by using the closed captioning script of the video program.

10  
11    **BACKGROUND OF THE INVENTION**

12            Conventional broadcast television is a non-interactive form of home  
13     entertainment. Television signals are broadcast one-way over a broadcast network  
14     from a television station or cable provider to home television sets. Viewers  
15     passively watch the video content played on the television sets, with their only  
16     interactivity being channel selection.

17            With computers, TV-based video games, and other multimedia  
18     environments, home users have become accustomed to interacting with the content  
19     being displayed. It is common for a computer user to selectively control what,  
20     when, and how content is displayed. For example, a computer user perusing a  
21     CD-ROM program on the Civil War might select a topic on Robert E. Lee. The  
22     computer user can use a mouse or other pointing device to page through various  
23     screens portraying the life of the General, read textual descriptions of Lee's  
24     achievements, click on icons to activate audio and video clips of reenacted war  
25     scenes. The whole experience is interactive.

1       The Internet offers an interactive multimedia environment. With the swift  
2 expansion and popularity of the Internet, many users are becoming familiar with  
3 “surfing” the World Wide Web (“Web” or “WWW”) to locate information,  
4 conduct business transactions, obtain weather forecasts, conduct banking and other  
5 financial matters, shop for merchandise, and so forth. The user can locate and  
6 download files in essentially any data format (video, audio, graphical, text, etc.)  
7 from essentially anywhere in the world.

8       With such advances in interactive entertainment, there has been some effort  
9 to enhance traditional television video programming with supplemental content.  
10 One approach is to support a television broadcast with supplemental content made  
11 available on the Internet. As an example, MSNBC news, a cable news network  
12 jointly established by Microsoft Corporation and NBC, offers a 24-hour cable  
13 news program with concurrent postings at its Web site containing information  
14 supplementing the cable broadcast.

15       Many industry pundits believe that in the future the supplemental content  
16 will be offered concurrently with the broadcast television program on the same  
17 display device. For example, a home viewer watching an episode of Gilligan’s  
18 Island on the television set might be able to access target resources on the Internet  
19 which relate to Gilligan’s Island, or other matters, from the same television set. It  
20 would be beneficial to present or make available the supplemental content at  
21 specific time slots in the episode. When Gilligan ruins the Skipper’s hat, for  
22 example, a producer might want to display a hyperlink to a hat retailer for a brief  
23 interval while the episode continues to run. The user then has an opportunity to  
24 activate the link to call up the hat retailer web site and shop for a new hat.  
25

1 One primary problem to enhancing traditional broadcast video programs  
2 concerns synchronizing presentation of the enhancing content with specific  
3 junctures or scenes in the video programs. In many cases, the enhancing content is  
4 not linked or associated with the video program in any useful manner. In the  
5 Gilligan example, a hyperlink to the hat retailer has no built in association to the  
6 video program Gilligan's Island. To compound the problem, the enhancing  
7 content will most likely not be provided from the same source as the video  
8 program.

9 The inventor has conceived of a technique for synchronizing presentation  
10 of the enhancing content with specific scenes in the video programs.

## 11 12 **SUMMARY OF THE INVENTION**

13 This invention concerns a system and method for synchronizing enhancing  
14 content with primary content, such as broadcast television programs, using the  
15 closed captioning script of the primary content. In this manner, enhancements to  
16 the primary content are timely introduced at preselected phrases or raw data  
17 strings of the closed captioning script, and hence at desired junctures of the  
18 primary content.

19 According to one aspect of the invention, a producer of enhancing content  
20 obtains the closed captioning script for a video program, such as a traditional  
21 broadcast television show, or a cable movie, or a program recorded on video  
22 cassette. The producer uses a parsing application to parse the closed captioning  
23 script to identify one or more key phrases. Preferably, the parser returns a set of  
24 unique phrases, with each phrase having the same number of words, or a unique  
25

1 data character string, with each character string having the same length of  
2 characters.

3 The program enhancement producer decides at what points in the video  
4 program to introduce enhancing content. As possible examples, the enhancing  
5 content might be a hyperlink to a target resource on the Internet, or manipulation  
6 of the video window with concurrent introduction of text or graphical data, or  
7 launching an application. After the program enhancement producer outlines the  
8 placement of the enhancing content within the video program, the producer uses  
9 an authoring computer to associate supplemental data (e.g., a URL, a file name,  
10 etc.) used to activate the enhancing content with specific key phrases or character  
11 strings of the closed captioning script that correspond to the desired points in the  
12 program. The authoring computer creates a key phrase data file which contains a  
13 listing of the key phrases or character strings and their association to the  
14 supplemental data.

15 The key phrase data file is delivered to viewer computing units (e.g.,  
16 personal computer, television with set top box, etc.) at users' homes. For example,  
17 the data file can be delivered over the broadcast network used to transport the  
18 video program, over the Internet or other network, or through the mail on a storage  
19 disk.

20 When the program is played, a viewer computing unit equipped with the  
21 key phrase data file for that program begins to monitor the closed captioning  
22 script. The viewer computing unit has a key phrase detector to detect the key  
23 phrases or character strings listed in the key phrase data file. In one  
24 implementation, the key phrase detector is a parser which examines sequential  
25 groupings of words or characters and compares the groupings with the key phrases

1 in the data file to identify the key phrases. Upon detection of a particular key  
2 phrase, the key phrase detector accesses the key phrase data file to retrieve the  
3 supplemental data associated with the particular key phrase. The viewer  
4 computing unit executes an enhancement action according to the supplemental  
5 data to synchronize the enhancement action with scenes in the video program.

6 According to one implementation, the key phrase detector multicasts the  
7 enhancement action to a multicast address. A program enhancement listener  
8 listens to the multicast address to receive and handle any enhancement action  
9 supported by the supplemental data. The listener can be implemented as an  
10 ActiveX™ control embedded in a container, such as an HTML page, or as an  
11 application. Using multicasting as an interprocess communication tool within the  
12 viewer computing unit effectively decouples the key phrase detection activity from  
13 the content enhancement activity, allowing the content enhancement producers to  
14 concentrate only on what enhancement actions to make in conjunction with the  
15 supplemental data.

## 16 17 **BRIEF DESCRIPTION OF THE DRAWINGS**

18 Fig. 1 is a diagrammatic illustration of a system for delivering both primary  
19 and enhancing content to viewer computing units.

20 Fig. 2 is a block diagram of an authoring system for producing an enhanced  
21 program in which enhancing content is synchronized to key phrases in a closed  
22 captioning script of the program.

23 Fig. 3 is a flow diagram of steps in a method for producing an enhanced  
24 program according to one implementation.

1 Fig. 4 is a flow diagram of steps in a method for producing an enhanced  
2 program according to another implementation.

3 Fig. 5 is a diagrammatic illustration of a key phrase data structure which  
4 associates the key phrases of the closed captioning script with supplemental data  
5 used to enhance a program.

6 Fig. 6 is a block diagram of a viewer computing unit.

7 Fig. 7 is a flow diagram of steps in a method performed by the viewer  
8 computing unit for enhancing primary content with enhancing content.

9 Fig. 8 illustrates the operation of a closed captioning parser resident at the  
10 viewer computing unit to identify key phrases in the closed captioning script.

## 11 12 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

13 Conventional broadcast television signals are transmitted in a data format  
14 that is used to construct individual television frames. Each frame contains video  
15 image data (i.e., pixel data) used to create images on the television screen and non-  
16 image information used to control the presentation of the image, such as  
17 synchronization and timing information. The non-image information is primarily  
18 contained within the first twenty-one lines of the television frame. These upper  
19 twenty-one lines are referred to as the Vertical Blanking Interval (VBI), and are  
20 not displayed on the television. Instead, these lines coincide with the vertical  
21 refresh period in which the cathode ray tube of the television set is moved from  
22 the lower right hand corner of the screen upon completion of one frame to the  
23 upper left hand corner of the screen for commencement of the next frame.

24 Closed captioning data is broadcast in line 21 of the VBI. The closed  
25 captioning data provides a textual script of the audio content in the program. The

1 textual script can be displayed concurrently with the program to assist a deaf or  
2 hearing impaired audience understand the character dialog or narration.

3 The Television Decoder Circuitry Act of 1990 requires that all televisions  
4 made after 1993 of a size 13 inches or larger be equipped with closed captioning  
5 decoding circuitry. Newer video cassette recorders are also designed to capture  
6 and replay the closed captioning data for a closed captioning enabled program. As  
7 a result, closed captioning data is becoming increasingly prevalent on broadcast  
8 television shows, syndicated shows, cable movies, and pre-recorded programs on  
9 video cassettes or digital video disks. The National Captioning Institute in  
10 Washington, DC estimates that nearly 100% of prime time television shows and  
11 between 60%-70% of syndicated shows have closed captioning.

12 An aspect of this invention concerns exploiting closed captioning as a  
13 means to synchronize the presentation of enhancing content to specific dialog  
14 sequences in a program.

15 Fig. 1 shows a system 20 which provides an exemplary context for  
16 implementing aspects of the invention. System 20 provides a data delivery  
17 architecture for delivering primary content along with supplemental or enhancing  
18 content to multiple viewer computing units, or clients 22(1), 22(2), ..., 22(L), ...,  
19 22(M). The primary content is the main program to be presented to the viewer,  
20 and it supports a closed captioning script. One notable example of primary  
21 content is continuous video data. Broadcast television shows, transmitted cable  
22 shows, pre-recorded movies on video cassettes or digital video disks (DVDs), live  
23 media feeds (e.g., news, sports, debates, etc.), and the like are all examples of  
24 primary content in the form of continuous video programs that are often closed  
25 captioning enabled.



1 The clients 22(1)-22(M) can be implemented in a number of ways,  
2 including desktop computers, laptop computers, and computer enhanced television  
3 units (e.g., a television with a set top box, a television with set top box  
4 functionality built in, etc.). An example implementation in which a client is  
5 constructed as a broadcast-enabled personal computer is described below with  
6 reference to Fig. 6.

7 In the Fig. 1 implementation, the primary content is delivered to the clients  
8 22(1)-22(M) in one of two ways. The first way is to broadcast the primary content  
9 over a conventional broadcast network 24 (e.g., RF, satellite, cable, microwave,  
10 etc.) from a broadcast station or cable headend 26. This is the typical approach to  
11 delivering television and cable shows to audiences.

12 A second way is to deliver the primary content over a data network 28, such  
13 as the Internet, to a broadcast center 30, which then delivers the primary content  
14 over a unidirectional network 32 to the clients 22(1)-22(M). The data network 28  
15 can be implemented in a number of ways, including wire-based technologies (e.g.,  
16 fiber optic, cable, wire, etc.) and wireless technologies (e.g., satellite, RF,  
17 microwave, etc.). The data network 28 can further be implemented using various  
18 available switching technologies (e.g., ATM (Asynchronous Transfer Mode),  
19 Ethernet, etc.) and different data communication protocols (e.g., TCP/IP, IPX,  
20 etc.). In such protocols, the data is packaged in individual, fixed byte-size packets  
21 which are transmitted separately over the data network. The unidirectional  
22 network 32 can be implemented in a variety of ways, including conventional  
23 networks such as satellite, radio, microwave, cable, and so forth. The broadcast  
24 network 32 might also be implemented as a network which supports two-way  
25

1 communication, but can be used for unidirectional multicasting from the broadcast  
2 center 32 to the clients 22(1)-22(M) simultaneously.

3 For the second approach, one or more content servers 34(1)-34(K) serve the  
4 primary content over the data network 28 to the broadcast center 30. Content  
5 servers used to serve the primary content might be configured, for example, as  
6 continuous media file servers which serve data files at a constant data rate. An  
7 exemplary construction of a file server comprises a disk array of storage disks,  
8 with the data files striped across the storage disks, and one or more servers which  
9 cooperate together to serve the data files from the storage disks.

10 The broadcast center 30 includes a router 36, a signal generator 38, and a  
11 broadcast transmitter 40. The router 36 is coupled to the data network 28 to  
12 receive the content served from the content servers 34(1)-34(K). The router 36 is  
13 a final node of the data network 28 in which data communication is bi-directional  
14 to that point and unidirectional past that point. The router 36 is preferably  
15 configured as a bridge-router between the traditional data network 28 and the  
16 broadcast network 32. A bridge-router is capable of supporting video and audio  
17 broadcast transmission. Data is received at the router 36 and converted from the  
18 network packet format to a format appropriate for broadcast transmission. The  
19 signal generator 38 generates a broadcast signal with the data embedded thereon to  
20 carry the data over the broadcast network 32. The broadcast signal is passed to the  
21 transmitter 40 where it is broadcast over the broadcast network 32 to the clients  
22 22(1)-22(M).

23 System 20 also allows for the delivery of enhancing content to the clients  
24 22(1)-22(M). The enhancing content is used to enhance the primary content. The  
25 enhancing content can be supplied to the clients 22(1)-22(M) over the broadcast

1 networks 24, 32, or over the data network 28 from the content servers 22(1)-  
2 22(K). One or more of the content servers 34(1)-34(K) are used to serve the  
3 enhancing content, which may be in the form of audio, video, animation, bit maps  
4 or other graphics, applications or other executable code, text, hypermedia, or other  
5 multimedia types. As an exemplary implementation, the content servers 22(1)-  
6 22(K) used to serve the enhancing content are implemented as personal computers  
7 or workstations running a multitasking, disk-based operating system, such as  
8 Windows® NT from Microsoft Corporation.

9 As an alternative, the enhancing content might reside on a storage medium  
10 at the viewer's home, such as on a computer disk or a CD-ROM, which can be  
11 accessed during the playing of the primary content.

12 One example of enhancing content is a hyperlink that is timely displayed at  
13 a certain juncture of the primary content to allow a viewer to activate the hyperlink  
14 and access a target resource on the Internet which has additional or related  
15 information to the primary content. For instance, suppose the primary content is a  
16 television episode of Seinfeld, in which the character Jerry Seinfeld is wearing  
17 Levi® jeans. When Seinfeld first appears in a scene, a content enhancing  
18 producer might wish to timely introduce a URL (Universal Resource Locator) to a  
19 Web Page for Levi Strauss Corporation that has information about the particular  
20 Levi® jeans that Seinfeld is wearing.

21 Another example of enhancing content is to manipulate the manner in  
22 which the primary content is being displayed. For instance, a content producer  
23 might wish to modify the video window in which the primary content is being  
24 displayed and concurrently introduce text or graphical data alongside or overlaid  
25 atop the primary content. One possible implementation is to launch an Internet

1 Web browser which presents a hypermedia document, such as an HTML  
2 (HyperText Markup Language) page. Within the hypermedia document, the  
3 producer can specify display layout instructions prescribing how the enhancing  
4 content and primary content are to appear in relation to one another when  
5 displayed. A detailed description of this implementation is provided in co-pending  
6 Application Serial No. 08/623,610, entitled "Interactive Entertainment System For  
7 Presenting Supplemental Interactive Content Together With Continuous Video  
8 Programs," filed March 29, 1996, in the names of Dan Shoff, Valerie Bronson,  
9 Joseph Matthews, III, and Frank Lawler, and assigned to Microsoft Corporation.  
10 This application is hereby incorporated by reference.

11 Another example of enhancing content is to launch an application, such as a  
12 Web browser, or a word processing application, or electronic mail. For instance,  
13 suppose the primary content is a political discussion program. Near the end of the  
14 program, the producer would like to gather feedback from the viewing audience  
15 regarding the issues discussed on the show. Accordingly, the producer might  
16 timely launch an electronic mail program at a specific point near the end of the  
17 program to present a new mail message with the "To" address filled in. The  
18 viewer can add comments and send the e-mail message to the program's producer  
19 for immediate feedback.

20 An aspect of this invention concerns a technique for synchronizing the  
21 enhancing content with the primary content in a manner which is independent of  
22 how and when the enhancing content, or the primary content, are delivered to the  
23 viewer computing units. The technique takes advantage of the closed captioning  
24 script as the timing mechanism for synchronizing introduction of the enhancing  
25 content relative to the primary content.

1 In general, a content enhancing producer obtains the closed captioning  
2 script of the primary content and relates key phrases or unique character strings  
3 from the script to supplemental data used to activate the enhancing content. Then,  
4 while the primary content is playing, the clients monitor the closed captioning  
5 dialog to detect the key phrases or character strings and to activate the enhancing  
6 content. In this manner, the enhancing content is presented at specific dialog  
7 sequences monitored in the closed captioning script, which coincide with  
8 particular junctures in the primary content.

9 Fig. 2 shows a computerized authoring system 50 which can be used by a  
10 content enhancing producer to create enhanced programs in which enhancing  
11 content is synchronized with scenes in a video program or other primary content.  
12 Authorizing system 50 is shown implemented as a personal computer or  
13 workstation having a processor 52, volatile memory 54 (e.g., RAM), and program  
14 memory 56 (e.g., hard disk, floppy disk, flash, ROM, etc.). An electronically  
15 readable version of the program's closed captioning script 58 is loaded into the  
16 program memory 56. A parser 60 is shown implemented as a computer software  
17 program stored in memory 56 and executable on the processor 52.

18 Fig. 3 shows a method for producing an enhanced program using the  
19 authoring system 50. The producer first obtains a copy of the closed captioning  
20 script for a program and loads the closed captioning script 58 in the authoring  
21 computer 50. At step 70 in Fig. 3, the parser 60 parses the closed captioning  
22 script 58 to identify one or more key phrases. The parser 60 is configured to  
23 compile a set of unique key phrases. Preferably, each key phrase has the same  
24 number of words. Consider the following example of a greeting dialog between  
25 two characters as presented in a fictional closed captioning script:

1  
2 Hi, how are you?

3 Oh, hi how are you?

4 I'm fine thanks.  
5

6 The parser 60 first determines the minimum number of words required to  
7 create unique phrases by trying different word lengths and checking for  
8 duplication. In this example, five word phrases are used. Phrases having a four or  
9 less word length result in duplication. For instance, the four word phrase "hi how  
10 are you" is duplicated in the short dialog.

11 Once the minimum length is determined, the parser 60 returns a set of  
12 unique phrases with each new phrase starting at sequential words in the dialog.  
13 From the above greeting dialog, the parser 60 returns the following set of unique  
14 phrases:  
15

16 hi how are you oh

17 how are you oh hi

18 are you oh hi how

19 you oh hi how are

20 oh hi how are you

21 hi how are you i'm

22 how are you i'm fine

23 are you i'm fine thanks  
24  
25

1       The parser 60 can also be configured to create unique character strings from  
2 the raw closed captioning data. For instance, for the text “Hi, how are you?”, the  
3 raw data might be “@!)(HI&,%!HOW~!@#ARE&!!YOU”. The non-  
4 alphanumeric characters are control characters which prescribe the positioning and  
5 formatting information. The parser 60 creates unique character strings that have  
6 the same character length. Rather than keying on the words themselves, the raw  
7 character stream is monitored to find the unique character strings.

8       For purposes of this disclosure, the term “phrase” is meant to include both  
9 word sequences of text (e.g., “oh hi how are you”) and character strings of raw  
10 data (e.g., “!OH@!)(HI&,%!HOW~!@”).

11       After compiling the key phrases, the parser 60 outputs a file containing the  
12 set of unique phrases.

13       It is noted that, rather than the parser 60, other types of key phrase  
14 identifiers can be used to identify key phrases in the closed captioning script. For  
15 example, the processor might be directed to search the closed captioning script for  
16 a single word, or a set of words, spoken by one or more characters to which the  
17 producer wants to introduce enhancing content.

18       At step 71 in Fig. 3, the producer determines at which point in the program  
19 to insert enhancing content. Suppose, for example, the author wants to display a  
20 hyperlink to a Web site for a greeting card company during the greeting scene in  
21 the video program. The author might choose the phrase “oh hi how are you” as  
22 the trigger for displaying the hyperlink. Accordingly, the author uses the  
23 authoring computer 50 to insert supplemental data in the form of a URL at the  
24 appropriate place in the closed captioning script. The revised script might read:  
25

1                   Hi, how are you?

2                   Oh, hi how <www.greetingcardco.com> are you?

3                   I'm fine thanks.

4  
5           After the producer has added all the enhancing content, the authoring  
6 computer 50 extracts the supplemental data and associates them with the  
7 corresponding key phrases (step 72 in Fig. 3). In this example, the authoring  
8 computer 50 retrieves the URL "www.greetingcardco.com" from the parser output  
9 file and links or otherwise associates it with the phrase "oh hi how are you" as  
10 follows:

11  
12                   oh hi how are you=www.greetingcardco.com

13  
14           As another example, suppose the author wants to launch an application at  
15 the response "I'm fine thanks." The authoring computer 50 might create the  
16 association:

17  
18                   are you i'm fine thanks=application.exe

19  
20           At step 73 in Fig. 3, the authoring computer 50 creates a key phrase data  
21 file which contains the supplemental data associated with the key phrases. This  
22 key phrase data file, referenced as number 62 in Fig. 2, is stored in memory 56  
23 during creation. The key phrase data file is subsequently given to the viewer  
24 computing units 22(1)-22(M) for use in decoding the closed captioning script  
25 when the primary content is playing to enhance the primary content.



1       The Fig. 3 method creates a data file containing a list of all unique key  
2 phrases in the closed captioning script. In another implementation, the authoring  
3 computer 50 automatically creates a reduced set of key phrases, on an “as needed”  
4 basis, which correspond to specific discrete points in the script for introduction of  
5 enhancing content.

6       Fig. 4 shows the alternative method for producing an enhanced program  
7 using the authoring system 50. As before, the content enhancing producer obtains  
8 a copy of the closed captioning script 58 and loads it in the authoring computer 50.  
9 At step 74, the producer reads through the closed captioning script (and perhaps,  
10 concurrently views the program) and identifies spots in the script for introducing  
11 enhancing content. The producer might identify such spots by simply clicking a  
12 mouse button at the particular place as the script is running. In response, the  
13 authoring computer marks the identified spot with an entry in a separate data file  
14 (step 75). The entry specifies the byte offset from the start of the script, as  
15 follows:

16  
17               byte offset into script file <tab> {place-holder 1}  
18               next byte offset into script file <tab> {place-holder 2}

19  
20       This new place holder data file contains references to a set of discrete  
21 points in the closed captioning script at which the producer intends to introduce  
22 enhancing content. The place-holders are monotonically incremented for each  
23 entry, and will eventually be replaced with the supplemental data for the  
24 enhancing content, such as a URL, trigger, or application name.  
25

1       At step 76 in Fig. 4, the parser 60 determines a minimum phrase length  
2       need to uniquely identify phrases at the discrete points of the script. For a given  
3       point, the parser returns a minimum phrase length necessary to uniquely identify  
4       that point in the script. The parser then determines an overall minimum phrase  
5       length based on the minimum lengths for each point (step 77 in Fig. 4). That is,  
6       the minimum phrase length for the script is equal to the maximum phrase length  
7       for any given point entry in the place holder file. The minimum phrase length may  
8       be expressed in terms of a number of words, or a number of characters, or a  
9       number of bytes.

10       Using the place holder file and minimum phrase length, the authoring  
11       computer traverses the closed captioning script and automatically identifies key  
12       phrases of the prescribed length at the selected spots in the script (step 78 in Fig.  
13       4). For each entry in the place holder file, the authoring computer skips to the byte  
14       offset in the script, and identifies a key phrase having the minimum phrase length  
15       at that particular spot. This key phrase is then associated with the place-holder, or  
16       supplemental data related to the place holder. As a result, the authoring computer  
17       automatically generates the key phrase data file 62 containing the key phrases  
18       associated with the supplemental data (step 79 in Fig. 4).

19       Fig. 5 shows an exemplary data structure for the key phrase data file 62.  
20       The data structure 62 includes key phrase data fields 80(1), 80(2), ..., 80(S) which  
21       contain key phrases 0-S that have been abstracted from a closed captioning script  
22       for use as enhancing content triggers. It is noted that the authoring computer  
23       might compute hashes of the key phrases to reduce the size of the data file and  
24       improve matching speed at the client.  
25

1       The data structure 62 also has supplemental data fields 82(1), 82(2), ...,  
2 82(S) which contain supplemental data 0-S for enhancing the primary content.  
3 The key phrase data structure 62 is organized in a manner that associates  
4 supplemental data 0-S in the supplemental data fields 82(1)-82(S) with  
5 corresponding key phrases 0-S in the key phrase data fields 80(1)-80(S). The key  
6 phrase data structure 62 also has a minimum phrase length data field 84 which  
7 contains the minimum number of words or minimum number of characters (or  
8 data bytes) in each key phrase 0-S.

9       According to the above implementations, the supplemental data is not  
10 actually added to the closed captioning script. Rather, the author creates a  
11 separate data file 62 that associates key phrases appearing in the closed captioning  
12 script with supplemental data used to call enhancing content. This is  
13 advantageous because the enhanced content producers can be independent of the  
14 producers of the primary content. The enhanced content producers merely need a  
15 copy of the closed captioning transcript to aid them in creating the enhancing  
16 content, but they do not ever change or modify the closed captioning transcript.  
17 Hence, they can operate independently of the primary content producers.

18       Another advantage is that the closed captioning script is almost always  
19 carried with the primary content to the end viewer, even though other lines of the  
20 Vertical Blanking Interval may be stripped away during rebroadcast. The  
21 enhancing content can be delivered independently of the primary content and  
22 synchronized at the viewer computing unit using the closed captioning script  
23 which accompanies the primary content. Additionally, most modern video  
24 cassette recorders are designed to capture the closed captioning script along with  
25 the primary content during recording. Thus, even during playback of a recorded

1 program, the closed captioning script is present to provide the timing mechanism  
2 for the enhancing content.

3 The key phrase data file created by the content enhancing producer is  
4 supplied to interested viewers. The key phrase data file can be delivered in a  
5 number of ways, such as broadcasting the file over the broadcast network used to  
6 carry the primary content, or multicasting the file to a multicast address to which  
7 the client listens, or posting the file at a publicly accessible Web site on the  
8 Internet, or supplying the file to the viewer on a computer disk or other storage  
9 medium.

10 In another implementation, the supplemental data might be embedded  
11 directly in the closed captioning script, rather than being linked to the key phrases  
12 through a data file. In this implementation, the producer inserts the supplemental  
13 data at key phrases in the transcripts. The supplemental data is formatted to be  
14 identified as such, so that the viewer computing unit does not display the  
15 supplemental data as part of the closed captioning text. Exemplary modifications  
16 that could be made to the closed captioning script include insertion of hyperlinks  
17 in the closed captioning script, insertion of replaceable key-phrases with monikers,  
18 and insertion of hidden or special characters to which supplemental data is keyed.  
19 However, embedding supplemental data directly into the transcript is in some  
20 ways less preferable because it requires cooperation between the primary content  
21 producers and the enhanced content producers. As a result, the enhanced content  
22 producers lose some of their freedom to create, while other enhanced content  
23 producers may be prevented from participating at all.

24 In another embodiment, the authoring computer system might be  
25 configured to write out the entire closed captioning script along with timing

1 information of the script relative to the video content (e.g., frame numbers). The  
2 closed captioning is stored as a text file, and the video is stored in a digital format,  
3 such as an AVI file. For each word in the closed captioning transcript, the  
4 authoring system writes the associated video frame number. The producer can  
5 then select places to insert enhancing content using the video itself, with the  
6 authoring system linking the enhancing content to the appropriate phrases in the  
7 closed captioning script.

8 Now, suppose that a viewer decides to watch a particular primary content  
9 that is capable of being enhanced. For purposes of continuing discussion, suppose  
10 that the primary content is delivered over a broadcast network and that the viewer  
11 has already been supplied with the key phrase data file 62.

12 Fig. 6 shows a viewer computing unit or client 22(1) constructed as a  
13 broadcast-enabled computer according to one exemplary implementation. It  
14 includes a central processing unit 90 having a processor 92 (e.g., x86 or Pentium®  
15 microprocessor from Intel Corporation), volatile memory 94 (e.g., RAM), and  
16 program memory 96 (e.g., ROM, disk drive, floppy disk drive, CD-ROM, etc.).  
17 The client 22 (1) has one or more input devices 98 (e.g., keyboard, mouse, etc.), a  
18 computer display 100 (e.g., VGA, SVGA), and a stereo I/O 102 for interfacing  
19 with a stereo system.

20 The client 22(1) includes a broadcast receiver 104 (e.g., satellite dish  
21 receiver, RF receiver, microwave receiver, multicast listener, etc.) and a tuner 106  
22 which tunes to appropriate frequencies or addresses of the broadcast network 24,  
23 32 (Fig. 1). The tuner 106 can be configured to receive the primary content in a  
24 particularized format, such as MPEG-encoded digital video and audio data. The  
25 client 22(1) also has a modem 108 which provides access to the data network 28

1 (Fig. 1). For other implementations, the modem 58 might be replaced by a  
2 network card, or an RF receiver, or other type of port/receiver which provides  
3 access to a compatible data network.

4 The client 22(1) runs an operating system (not shown) which supports  
5 multiple applications. The operating system is preferably a multitasking operating  
6 system which allows simultaneous execution of multiple applications. The  
7 operating system employs a graphical user interface windowing environment  
8 which presents the applications or documents in specially delineated areas of the  
9 display screen called "windows." One preferred operating system is a Windows®  
10 brand operating system sold by Microsoft Corporation, such as Windows® 95 or  
11 Windows® NT or other derivative versions of Windows®. It is noted, however,  
12 that other operating systems which provide windowing environments may be  
13 employed, such as the Macintosh operating system from Apple Computer, Inc. and  
14 the OS/2 operating system from IBM.

15 One example implementation of a broadcast-enabled PC is described in a  
16 co-pending U.S. Patent Application Serial No. 08/503,055, entitled "Broadcast-  
17 Enabled Personal Computer," filed January 29, 1996 in the names of Gabe L.  
18 Newell, Dan Newell, Steven J. Fluegel, David S. Byrne, Whitney McCleary,  
19 James O. Robarts, Brian K. Moran; William B. McCormick, T.K. Backman,  
20 Kenneth J. Birdwell, Joseph S. Robinson, Alonzo Gariepy, Marc W. Whitman,  
21 and Larry Brader. This application is assigned to Microsoft Corporation, and is  
22 incorporated herein by reference.

23 The client 22(1) is illustrated with two software programs: a closed  
24 captioning parser 110 and an HTML page with an embedded multicast listener  
25 112. Each program is stored in program memory 96, loaded into volatile memory

1 94 when launched, and executed on the processor 92. The key phrase data file 62  
2 is also shown stored in the program memory 96. The closed captioning parser  
3 110 is configured to monitor the closed captioning script as the video program is  
4 played to detect the key phrases listed in data file 62.

5 Fig. 7 shows a method for enhancing the primary content with  
6 supplemental data. At step 120, the client prepares for playing an enhanced  
7 program by initializing the closed captioning parser 110 to the minimum word  
8 length or character count of the key phrases. This initialization sets the parser 110  
9 to monitor the closed captioning script in successive groups of words equal to this  
10 word length or character strings equal to the character count. The client obtains  
11 the key phrase word length from the minimum phrase length data field 84 of the  
12 data structure 62 (Fig. 5).

13 At step 122 in Fig. 7, the client 22(1) plays the primary content on the  
14 display 100. In this example, the receiver 104 receives the primary content from  
15 the broadcast network and passes it to the central processing unit 90. The CPU 90  
16 strips the non-video data in the Vertical Blanking Interval and passes the video  
17 data to video display drivers for presentation on the display 100. The primary  
18 content contains a closed captioning script which is contained as part of the  
19 Vertical Blanking Interval. The text of the closed captioning script may or may  
20 not be displayed on display 100 concurrently with the primary content in  
21 customary fashion.

22 As the primary content plays, the closed captioning parser 110 monitors the  
23 successive word groups in the closed captioning script (step 124 in Fig. 7). The  
24 parser 110 compares each word group with the list of key phrases in the key  
25 phrase data fields 80(1)-80(S) of the data structure 62 (step 126 in Fig. 7). If no

1 match occurs (i.e., the “no” branch from step 128), the parser 110 continues to the  
2 next word group (step 130). It is noted that, if the data file contains hash values of  
3 the key phrases, the parser 110 may need to compute hashes of each word group  
4 for comparison to the stored hash values.

5 Fig. 8 illustrates this process for parsing the closed captioning script using  
6 the greeting dialog from the examples given above. The parser 110, which is  
7 initialized to a word length of five, examines successive groups of five words in  
8 the closed captioning script 140. The first group 142 is the five word phrase “hi  
9 how are you oh.” This phrase is compared to the key phrases in data structure 62  
10 and no match occurs. Thus, the parser 110 moves to the next group 144 which  
11 provides the five word phrase “how are you oh hi.” Once again, the phrase is  
12 compared to the key phrases and no match occurs. The process is repeated for the  
13 next group 146, and for successive groups thereafter.

14 When a group of words matches a key phrase in the data structure 62 (i.e.,  
15 the “yes” branch from step 128), the parser 110 looks up in the data file for the  
16 supplemental data corresponding to the matched key phrase. In this manner, the  
17 data file is utilized as an association look-up table. The supplemental data is  
18 associated with the key phrases through the inherent corresponding field  
19 arrangement of the data structure 62. The parser 110 retrieves the supplemental  
20 data from the key phrase data file 62 (step 132 in Fig. 7). In the continuing  
21 example, the parser 110 detects the phrase “oh hi how are you” which matches a  
22 key phrase stored in data structure 62. The parser then retrieves the hyperlink  
23 “www.greetingcardco.com,” which is associated with the phrase, from the data  
24 structure 62. The client can now use the supplemental data to activate an  
25



1 enhancing action which enhances the primary content, such as displaying the  
2 hyperlink on the screen along with the primary content.

3 According to an aspect of the invention, the client employs multicasting as  
4 an interprocess communication technique. At step 134 in Fig. 7, the parser 110  
5 sends the supplemental data to a multicast address monitored locally by the client.  
6 The parser 110 then continues to the next word group (step 130 in Fig. 7).

7 Meanwhile, the HTML container with the program enhancement listener  
8 112 listens to the multicast address to receive the supplemental data (step 136 in  
9 Fig. 7). Upon receiving the supplemental data, the listener operates on the  
10 supplemental data to perform the enhancing action, such as displaying a hyperlink,  
11 or launching an application, or displaying supplemental data concurrently on the  
12 screen with the primary data (step 138 in Fig. 7). In this manner, the enhancement  
13 action is synchronized with the particular scene in which the dialog “oh hi how are  
14 you” takes place.

15 More specifically, the listener is preferably implemented as an ActiveX™  
16 control which sits in a container, such as the HTML page, or an application.  
17 ActiveX™ is a technology developed and marketed by Microsoft Corporation.  
18 ActiveX™ controls are described in detail in a book entitled, Exploring ActiveX,  
19 by Shannon R. Turlington, Ventana Communications Group, Inc., copyright 1996,  
20 which is hereby incorporated by reference. The listener examines the  
21 supplemental data received at the multicast address and decides what action to  
22 take.

23 The supplemental data can be encoded to indicate its type. For example,  
24 supplemental data in plaintext means it is a hyperlink (e.g.,  
25 www.greetingcardco.com); supplemental data enclosed in quotes means it is an

1 executable file (e.g., "application.exe"); and supplemental data enclosed in curly  
2 brackets means it is a trigger for arbitrary text or graphical data (e.g., {text}).  
3 Depending upon the type of supplemental data, the listener takes one of the  
4 following actions: (1) instructs a Web browser to bring up a URL, (2) expose the  
5 arbitrary message directly to the container, or (3) launch an application. The type  
6 identifiers explained above are examples, as any arbitrary convention for  
7 identifying data type may be used.

8 With the multicast listener and interprocess communication technique, the  
9 enhancement action is decoupled from the parser activity for detecting key  
10 phrases. This is advantageous from a production standpoint as it permits the  
11 enhanced content producers to concentrate solely on the enhancing content to be  
12 activated by the supplemental data, without regard to how and when the parser  
13 detects the key phrases or retrieves the supplemental data.

14 The invention is advantageous in that it leverages the existing closed  
15 captioning available in most programs as a timing mechanism for synchronizing  
16 enhancing content with the primary content. With this method, the program can  
17 be started mid-stream and the enhancing content for the remaining portion will  
18 still be timely cued at appropriate junctures of the primary content.

19 The implementation described above is explained in the context of  
20 receiving broadcast programs, such as television shows, from a broadcast network  
21 and the enhancing content from content servers on the Internet. This is but one  
22 example as other example implementations exist. For instance, another example  
23 might be to locally supply the primary content and closed captioning script from a  
24 video cassette and the supplemental data from a separate computer disk, such as a  
25 CD-ROM.

1        In compliance with the statute, the invention has been described in  
2 language more or less specific as to structural and methodical features. It is to be  
3 understood, however, that the invention is not limited to the specific features  
4 described, since the means herein disclosed comprise preferred forms of putting  
5 the invention into effect. The invention is, therefore, claimed in any of its forms  
6 or modifications within the proper scope of the appended claims appropriately  
7 interpreted in accordance with the doctrine of equivalents.